


TF 25T

TF 40T

TF 90T

Output	: Upto 25,000 Capsules/ hour for power filling : Upto 23,000 Capsules/ hour for pellet filling : Upto 13,000 Capsules/ Tablet filling (Single tablet)	: Upto 40,000 Capsules/ hour for power filling : Upto 35,000 Capsules/ hour for pellet filling	: Upto 90,000 Capsules/ hour for power filling : Upto 80,000 Capsules/ hour for pellet filling : Upto 50,000 Capsules/ Tablet filling (Single tablet)
Electric Supply	: 415V, 3 Phase +N +E, 50 Hz, A.C.	: 415V, 3 Phase +N +E, 50 Hz, A.C.	: 415V, 3 Phase +N +E, 50 Hz, A.C.
Main Motor	: 1.1kW(1.5 HP) at 750 rpm.	: 1.5kW variable speed	: 1.5kW(2HP) at 1440 rpm.
Power Feed Motor		: 0.18 kW	
Vacuum Required (Capsule Separation)	: 575 LPM at 18° of mercury	: 1100 LPM at 26° of mercury	: 1100 LPM at 26° of mercury
Vacuum Required (Cleaning)	: 2800 LPM at 4° of mercury	: 2800 LPM at 4° of mercury	: 2800 LPM at 4° of mercury
Compressed Air	: 140 LPM at 6kg/cm ²	: 200 LPM at 5-7kg/cm ²	: 300 LPM at 6kg/cm ²
Connected Load	: 1.5kW (2HP) approx. form machine only		: 2.0kW (3HP) approx. form machine only
Connected Load	: 7.5kW (10 HP) approx. form machine with vacuum pump, air compressor & ADU		: 8.0kW (11 HP) approx. form machine with vacuum pump, air compressor & ADU
Dimensions (L x W x H)	: 1210mm x 955mm x 1900mm	: 1210 mm x 955mm x 1900mm	: 1650 mm x 1290mm x 2050mm
Gross Weight	: 1000 kgs	: 1100 kgs	: 2350 kgs
Shipping Dimension (L x W x H)	: 1500mm x 1200mm x 2200mm	: 1600mm x 1400mm x 2100mm	: 2140mm x 1600mm x 2200mm
Shipping Weight	: 1200 kgs Approx	: 1300 kgs Approx	: 2550 kgs Approx